

## Ebosoft LT

softener

<b>Chemical composition</b>	blend of synthetic sulfoester derivates
<b>Active matter</b>	approx. 35 %
<b>Appearance</b>	clear, viscous
<b>pH - value (1:10)</b>	5.0 - 7.0
<b>Charge</b>	anionic
<b>Stability</b>	stable to acids and salts under usual tannery conditions, stable in chrome and pickle liquors
<b>Dilution</b>	1 : 3 with water of 50 °C - 60 °C

### Field of application

Softener for all kinds of soft and fluffy leathers.

### Properties

- excellent softness
- enhances tear resistance
- gives more fullness
- very good leveling during dyeing
- high emulsifying power, stabilizes fatliquor mixtures

### Application


Ebosoft LT should be used in the neutralization or in combination with fatliquors.

Percentage is based on the shaved weight.

Neutralization	Ebosoft LT	2.0 % - 3.0 %
Fatliquoring	Ebosoft LT	2.0 % - 4.0 %

#### Remark

Ebosoft LT is a technical product and variations in colour and viscosity can happen. The properties for application are not touched by this.



#### Storage temperature

Storage at temperatures between 5 °C and 40 °C.



#### Shelf life

Up to 12 months in the original sealed packing.



#### Usage

Stir before use.

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.